

# Y-C6-DEV Development System



## Key Feature

- Jetson™ Orin NX: 157/117 TOPS, 16/8GB LPDDR5
- Jetson™ Orin Nano: 67/34 TOPS, 8/4GB LPDDR5
- Jetson™ Xavier NX: 21 TOPS, 16/8GB LPDDR4x, 16GB eMMC
- Jetson™ TX2 NX: 1.33 TFLOPS, 4GB LPDDR4, 16GB eMMC
- Jetson™ Nano: 0.5 TFLOPS, 4GB LPDDR4, 16GB eMMC
- Rich I/O: HDMI, RJ45, USB3.0 Type-A, Micro USB, RTC, GPIO
- Expansion Slots: miniPCIe (USB2.0 & PCIe x1)
- Camera: 2× 2 Lane MIPI CSI
- Operating Temperature: -25°C ~ +65°C
- Input Voltage: DC 9V ~ 24V
- Pre-installed Ubuntu


## Introduction

Y-C6-DEV is an edge AI computing development kit supporting NVIDIA® Jetson™ Nano/TX2 NX/Xavier NX/Orin Nano/Orin NX system-on-modules, providing graded AI performance from 0.5 TFLOPS to 117 TOPS to match diverse edge computing requirements. Its compact and highly integrated design meets industrial-grade demands for high performance, low power consumption and harsh environment adaptability.

The kit integrates dual high-performance miniPCIe slots supporting standard function modules for flexible upgrade and customization. It is widely used in smart logistics, retail, industrial inspection and smart agriculture to accelerate AI deployment.



Website



Logistics Robot



Agriculture Machinery



Medical Instrumentation



Collaborative Robot

## Specifications

Module	Jetson Nano	Jetson TX2 NX	Xavier NX 16/8GB	Jetson Orin Nano 8GB	Jetson Orin Nano 4GB	Jetson Orin NX 16GB	Jetson Orin NX 8GB
<b>AI Performance</b>	0.5 TFLOPS	1.33 TFLOPS	21TOPS	67 TOPS	34 TOPS	157 TOPS	117 TOPS
<b>GPU</b>	128-core NVIDIA Maxwell™ architecture GPU	256-core NVIDIA Pascal™ architecture GPU	384-core NVIDIA Ampere architecture GPU with 48 Tensor Cores	1024-core NVIDIA Ampere architecture GPU with 32 Tensor Cores	512-core NVIDIA Ampere architecture GPU with 16 Tensor Cores	1024-core NVIDIA Ampere architecture GPU with 32 Tensor Cores	
<b>CPU</b>	Quad-core ARM® Cortex®-A57 MPCore processor	A57 MPCore processor Dual-core NVIDIA Denver™ 2 64-bit CPU and 4 cores Arm® Cortex®-A57 MPCore processor	6-core NVIDIA CarmelArm®v8.2 64-bit CPU 6MB L2 + 4MB L3	6-core Arm® Cortex® -A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3		8-core Arm®Cortex® -A78AE v8.2 64-bit CPU 2MB L2 + 4MB L3	6-core Arm®Cortex® -A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3
<b>Memory</b>	4GB 64-bit LPDDR4 25.6GB/s	4GB 128-bit LPDDR4 25.6GB/s	16/8GB 128 -bit LPDDR4x 59.7GB/s	8GB 128-bit LPDDR5 102 GB/s	4GB 64-bit LPDDR5 51 GB/s	16GB 128-bit LPDDR5 102.4GB/s	8GB 128-bit LPDDR5 102.4GB/s
<b>Storage</b>	16GB eMMC			(Supports external NVMe)			
<b>Video Encode</b>	1x 4K30 (H.265) 2x 1080p60 (H.265)	1x 4K60 (H.265) 3x 4K30 (H.265) 4x 1080p60 (H.265)	2x 4K60 (H.265) 4x 4K30 (H.265) 10x 1080p60 (H.265) 22x 1080p30 (H.265)	1080p30 supported by 1-2 CPU cores		1x 4K60 (H.265)、3x 4K30 (H.265) 6x 1080p60 (H.265)、12x 1080p30 (H.265)	
<b>Video Decode</b>	1x 4K60 (H.265) 4x 1080p60 (H.265)	2x 4K60 (H.265) 7x 1080p60 (H.265) 14x 1080p30 (H.265)	2x 8K30 (H.265) 6x 4K60 (H.265) 12x 4K30 (H.265) 22x 1080p60 (H.265) 44x 1080p30 (H.265)	1x 4K60 (H.265)、2x 4K30 (H.265) 5x 1080p60 (H.265)、11x 1080p30 (H.265)		1x 8K30 (H.265)、2x 4K60 (H.265) 4x 4K30 (H.265)、9x 1080p60 (H.265) 18x 1080p30 (H.265)	
<b>Display</b>	1 x HDMI						
<b>USB</b>	1x USB3.0 Type-A、1x Micro USB						
<b>Networking</b>	1x RJ45						
<b>SD Card</b>	1x micro SD			—			
<b>Button</b>	1x Recovery、1x Reset						
<b>Camera</b>	2x 2 Lane MIPI CSI						
<b>Expansion</b>	1x miniPCIe 1x nano SIM	2x miniPCIe、1x nano SIM					
<b>Functional Signals</b>	1x SPI、4x GPIO 1x I2C	1x CAN、1x SPI、4x GPIO、1x I2C					
<b>Serial Ports</b>	2x RS232、1x TTL						
<b>Temperature</b>	-25°C~+65°C						
<b>Dimensions</b>	120mm × 80mm × 36.9mm						
<b>Power</b>	DC+9V~ +24V						
<b>Weight</b>	158g						

## Interfaces

