

8F4E1

Edge AI Box



Key Feature

- Jetson™ AGX Orin: 275/200 TOPS, 64/32GB LPDDR5, 64GB eMMC;
- Jetson™ AGX Xavier: 32 TOPS, 64/32GB LPDDR4X, 32GB eMMC
- Display: 1 × HDMI
- Rich I/O: 2 × RJ45, 2 × USB Type-A, 1 × Micro SD, 4 × GPIO, 2 × CAN, 2 × RS232
- Expansion: Built-in 2 × full-size miniPCle, 2 × M.2 M 2280, 1 × PCIe x16
- Operating Temperature: -25°C ~ +65°C
- Input Voltage: AC 220V
- Pre-installed Ubuntu

Introduction

The 8F4E1 is a high-performance edge AI computing device powered by NVIDIA® Jetson™ AGX Orin/ AGX Xavier, offering 32~275 TOPS AI performance for education, research, industrial automation, smart city and energy scenarios.

It provides rich I/O and flexible expansion for Ethernet, storage, communication and control cards. When equipped with AGX Xavier, it supports NVIDIA RTX 6000/A6000 GPUs and is fully compatible with NVIDIA Clara AGX SDK for fast AI development.



Website



Intelligent Patrol



Intelligent Traffic Analysis



Visual quality inspection



Machine arm control

Specifications

Module	Jetson AGX Orin 64GB	Jetson AGX Orin 32GB	Jetson AGX Xavier 64GB	Jetson AGX Xavier 32GB
AI Performance	275 TOPS	200 TOPS	32 TOPS	
GPU	2048-core NVIDIA Ampere GPU with 64 Tensor Cores	1792-core NVIDIA Ampere GPU with 56 Tensor Cores	512-core NVIDIA Ampere GPU with 64 Tensor Cores	
CPU	12-core Arm® Cortex® -A78AE v8.2 64-bit CPU 3MB L2 + 6MB L3	8-core Arm® Cortex® -A78AE v8.2 64-bit CPU 2MB L2 + 4MB L3	8-core Arm® Cortex® -A78AE v8.2 64-bit CPU 2MB L2 + 4MB L3	
Memory	64GB 256-bit LPDDR5 204.8GB/s	32GB 256-bit LPDDR5 204.8GB/s	64GB 256-bit LPDDR4x 136.5GB/s	32GB 256-bit LPDDR4x 136.5GB/s
Storage	64GB eMMC 5.1		32GB eMMC 5.1	
Video Encode	2x 4K60 (H.265)、4x 4K30 (H.265) 8x 1080p60 (H.265) 16x 1080p30 (H.265)	1x 4K60 (H.265)、3x 4K30 (H.265) 6x 1080p60 (H.265) 12x 1080p30 (H.265)	4x 4K60 (H.265)、8x 4K30 (H.265) 16x 1080p60 (H.265)、32x 1080p30 (H.265)	
Video Decode	1x 8K30 (H.265)、3x 4K60 (H.265) 7x 4K30 (H.265) 11x 1080p60 (H.265) 22x 1080p30 (H.265)	1x 8K30 (H.265)、2x 4K60 (H.265) 4x 4K30 (H.265)、9x 1080p60 (H.265) 18x 1080p30 (H.265)	2x 8K30 (H.265)、6x 4K60 (H.265) 12x 4K30 (H.265)、26x 1080p60 (H.265) 52x 1080p30 (H.265)	
Display	1x HDMI2.0			
USB	2x USB3.0 Type-A、1x Micro USB(OTG)		1x USB3.0 Type-A、1x USB2.0 Type-A、1x Micro USB(OTG)	
Networking	2x RJ45		1x RJ45	
SD Card	1 x Micro SD			
Button	1 x Recovery 、 1 x Reset			
Expansion	2 x Overall Length mini PCIe、2 x M.2 M (2280)、1x PCIe16		1 x Overall Length mini PCIe、1 x M.2 M (2280)、1x PCIe16	
Other I/O	4 x GPIO、2 x CAN、2 x I2C、1 x SPI			
Serial Ports	2 x RS232、1 x Debug (UART)			
Temperature	-25°C ~ +65°C			
Dimensions	335mm×257mm×146 mm			
Power	AC +220V			
Weight	5500g			

Interfaces

